


Amortiguador de vibraciones


AWI




AWI R




tamaños de 15 a 27




tamaños de 38 a 50



tamaño 50-2



AWI L



N.º de pieza	Tipo	Carga $G_{min.} - G_{max.}$ [N]	A descargado	A* carga máxima	B	C	D	E	F
05 111 101	AWI 15R	180-400	68	55	22.5	45	7 × 10	50	65
05 121 101	AWI 15L	180-400	68	55	22.5	45	7 × 10	50	65
05 111 102	AWI 18R	350-850	88	70	30	60	9 × 15	60	80
05 121 102	AWI 18L	350-850	88	70	30	60	9 × 15	60	80
05 111 103	AWI 27R	650-1500	111	91	35	70	11 × 20	80	105
05 121 103	AWI 27L	650-1500	111	91	35	70	11 × 20	80	105
05 111 104	AWI 38R	1200-3000	150	122	47.5	95	13 × 20	100	125
05 121 104	AWI 38L	1200-3000	150	122	47.5	95	13 × 20	100	125
05 111 105	AWI 45R	2000-4800	177	145	55	110	13 × 26	115	145
05 121 105	AWI 45L	2000-4800	177	145	55	110	13 × 26	115	145
05 111 106	AWI 50R	4000-9600	194	159	60	120	17 × 27	130	170
05 121 106	AWI 50L	4000-9600	194	159	60	120	17 × 27	130	170
05 111 108	AWI 50-2R	6600-16000	194	159	60	120	17 × 27	130	170
05 121 108	AWI 50-2L	6600-16000	194	159	60	120	17 × 27	130	170

N.º de pieza	Tipo	H	K	L	M	N	x máx.	Peso [kg]	Frecuencia natural $G_{min.} - G_{max.}$ [Hz]	Estructura del material
05 111 101	AWI 15R	3	10	40	52	—	14	0.5	7.2-4.5	Fundición de acero inoxidable GX5CrNi19-10 (1.4308)
05 121 101	AWI 15L	3	10	40	52	—	14	0.5	7.2-4.5	
05 111 102	AWI 18R	3.5	14	50	67	—	19	0.9	6.5-3.7	
05 121 102	AWI 18L	3.5	14	50	67	—	19	0.9	6.5-3.7	
05 111 103	AWI 27R	4.5	17	60	80	—	22	1.9	6.0-3.7	
05 121 103	AWI 27L	4.5	17	60	80	—	22	1.9	6.0-3.7	
05 111 104	AWI 38R	6	21	80	104	40	31	4.5	5.2-3.2	
05 121 104	AWI 38L	6	21	80	104	40	31	4.5	5.2-3.2	
05 111 105	AWI 45R	8	28	100	132	58	35	7.8	5.0-2.8	
05 121 105	AWI 45L	8	28	100	132	58	35	7.8	5.0-2.8	
05 111 106	AWI 50R	12	40	120	165	60	38	12.8	4.8-2.8	
05 121 106	AWI 50L	12	40	120	165	60	38	12.8	4.8-2.8	
05 111 108	AWI 50-2R	12	45	200	250	70	38	20.3	4.8-2.8	
05 121 108	AWI 50-2L	12	45	200	250	70	38	20.3	4.8-2.8	

* carga de compresión $G_{max.}$ y compensación de flujo en frío (después de aproximadamente 1 año).

Si no se especifican otras unidades, los números indicados están en mm.

Los tamaños 50 y 50-2 pueden combinarse entre sí (alturas y comportamiento de funcionamiento idénticos).