


Elemento de suspensión de goma


DO-A




tamaños de 15 a 45




tamaños de 15 a 45



tamaño 50



tamaño 50



N.º de pieza	Tipo	ø A	B	D	E	F	□ S	G	H	L	L1	Peso [kg]
01 041 001	DO-A 15 × 25	5 ^{+0.5} ₀	10 ±0.2	28	25.5	53.5	15	—	—	25	30 ⁰ _{-0.3}	0.07
01 041 002	DO-A 15 × 40	5 ^{+0.5} ₀	10 ±0.2	28	25.5	53.5	15	—	—	40	45 ⁰ _{-0.3}	0.11
01 041 003	DO-A 15 × 60	5 ^{+0.5} ₀	10 ±0.2	28	25.5	53.5	15	—	—	60	65 ⁰ _{-0.3}	0.15
01 041 004	DO-A 18 × 30	6 ^{+0.5} ₀	12 ±0.3	34	31	65	18	—	—	30	35 ⁰ _{-0.3}	0.12
01 041 005	DO-A 18 × 50	6 ^{+0.5} ₀	12 ±0.3	34	31	65	18	—	—	50	55 ⁰ _{-0.3}	0.20
01 041 006	DO-A 18 × 80	6 ^{+0.5} ₀	12 ±0.3	34	31	65	18	—	—	80	85 ⁰ _{-0.3}	0.31
01 041 007	DO-A 27 × 40	8 ^{+0.5} ₀	20 ±0.4	47	44	91	27	—	—	40	45 ⁰ _{-0.3}	0.32
01 041 008	DO-A 27 × 60	8 ^{+0.5} ₀	20 ±0.4	47	44	91	27	—	—	60	65 ⁰ _{-0.3}	0.47
01 041 009	DO-A 27 × 100	8 ^{+0.5} ₀	20 ±0.4	47	44	91	27	—	—	100	105 ⁰ _{-0.3}	0.76
01 041 010	DO-A 38 × 60	10 ^{+0.5} ₀	25 ±0.4	63	60	123	38	—	—	60	70 ⁰ _{-0.3}	0.88
01 041 011	DO-A 38 × 80	10 ^{+0.5} ₀	25 ±0.4	63	60	123	38	—	—	80	90 ⁰ _{-0.3}	1.14
01 041 012	DO-A 38 × 120	10 ^{+0.5} ₀	25 ±0.4	63	60	123	38	—	—	120	130 ⁰ _{-0.3}	1.69
01 041 013	DO-A 45 × 80	12 ^{+0.5} ₀	35 ±0.5	85	73	150	45	—	—	80	90 ⁰ _{-0.3}	1.84
01 041 014	DO-A 45 × 100	12 ^{+0.5} ₀	35 ±0.5	85	73	150	45	—	—	100	110 ⁰ _{-0.3}	2.27
01 041 015	DO-A 45 × 150	12 ^{+0.5} ₀	35 ±0.5	85	73	150	45	—	—	150	160 ⁰ _{-0.3}	3.37
01 041 026	DO-A 50 × 120	M12	40 ±0.5	89	78	167	50	30	60	120	130 ⁰ _{-0.3}	3.30
01 041 029	DO-A 50 × 160	M12	40 ±0.5	89	78	167	50	30	60	160	170 ⁰ _{-0.3}	4.40
01 041 027	DO-A 50 × 200	M12	40 ±0.5	89	78	167	50	40	70	200	210 ⁰ _{-0.3}	5.50

Lista de pares y cargas en la página 2.3.

Si no se especifican otras unidades, los números indicados están en mm.

Estructura del material: DO-A 50 disponible con carcasas de fundición nodular bajo pedido